

SHORT COURSE: MINE WATER TREATMENT TECHNOLOGIES, CASE STUDIES, AND COSTS

CASE STUDY
SULFATE REMOVAL USING ADVANCED ETTRINGITE PROCESS

Scott Benowitz, P. E. / **W**ater **E**ngineering **T**echnologies, Inc.
4691 Shandalyn Lane / Bozeman, MT 59718 / +1 406 585 7101
wetsib@benowitz.net

Water
Engineering
Technologies, Inc.

ACKNOWLEDGMENTS

- Topic contributors:
 - Scott Benowitz, P.E., Water Engineering Technologies, Inc.
 - Kashi Banerjee, PhD, P.E. Veolia Water Technologies

CASE STUDY


SULFATE REMOVAL USING ADVANCED ETTRINGITE
PROCESS

TWO - STAGE SULFATE TREATMENT PILOT STUDY USING ADVANCED ETTRINGITE PROCESS

Overview:

- Reduces sulfate to 100- 200 mg/L by two stage process:
 - 1st Stage: CaSO_4 desaturation; SO_4 is reduced to <1500 mg/L
 - 2nd Stage: advanced chemical precipitation; SO_4 reduced to < 200 mg/l
- Treated effluent can be reused or discharged to environment.

TIMELINE OF TWO-STAGE PILOT STUDY



1ST STAGE IMPLEMENTATION

- Project site: copper mine in South America
- Tailing pond water contains high sulfate and calcium
- Project requires sulfate to < 250 mg/l; TDS to < 1,000 mg/l

1ST STAGE PILOT STUDY

Tailing Pond Water Characteristics:

Parameter	Value (mg/l unless indicated)	Parameter	Value (mg/l unless indicated)
pH	7.4 s.u.	Na	104
Mg	21	K	124
SO ₄	1,830	Ca	690
Fe	0.04	Alkalinity	28
Mn	0.17	TDS	3,070
Mo	0.27	Cations	40.02 meq/l
Al	0.05	Anions	44.04 meq/l

1ST STAGE PILOT STUDY

Pretreatment and membrane:

- Pretreatment includes iron addition, clarification, multi-media filtration and Green Sand filtration
 - Mo was reduced to < 0.05 mg/L
 - Fe < 0.3 mg/L
 - Mn <0.05 mg/L
- SDI = 3
- NF: Dow Filmtec

1ST STAGE PILOT STUDY

NF Permeate vs Discharge Standards

Parameters	Permeate (mg/l)	Discharge Standard (mg/l)
SO ₄	35	250
Cl	80	200
Ca	25	60
Al	<0.1	5
Fe	<0.01	5
Mn	<0.01	0.2
As	<0.005	0.1
Cd	<0.005	0.1
Cu	0.01	0.2



1ST STAGE PILOT STUDY

NF Reject Treatment Objectives:

- Precipitate SO_4 as CaSO_4
- Use lime or lime/ CaCl_2 as sources of Ca^{2+}
- Determine the impact of sludge recirculation ratio on CaSO_4 nucleation and crystal growth
- Ratio = Mass of solids [CaSO_4] in the recycle line / Mass of solids [CaSO_4] formed from the fresh wastewater [NF reject]
- Goal was to reduce SO_4 to $< 1,500 \text{ mg/L}$ as SO_4 (theoretical solubility limit)

1ST STAGE PILOT STUDY

- Calcium sulfate desaturation with sludge recirculation
- NF brine: sulfate - 3200 mg/L
- Desaturation process using Turbomix[®] Reactor with 30-minute reaction time followed by MULTIFLO[™] clarification for solid/liquid separation



1ST STAGE PILOT STUDY

1st stage test results:

- Calcium sulfate precipitation as a function of sludge recirculation ratio:

Sludge Recycle Ratio (Dry mass CaSO ₄ sludge to influent)	20:1	15:1	10:1	none
pH	9.3	9.3	9.2	9.3
Clarifier overflow SO ₄ , mg/l	1,250	1,100	1,200	2,000

2ND STAGE IMPLEMENTATION


- 2nd Stage Precipitation [Ettringite] Pilot
 - Site: Greene County, PA
 - ARD Water [Effluent from DenSludge™ HDS Process]
 - Study Period: 16 weeks

2ND STAGE OBJECTIVES

- Validate Sulfate Reduction Process: < 200 mg/l SO₄
- Validate Gibbsite Regeneration and Recovery
- Use Recovered Gibbsite to Precipitate Ettringite
- Process Optimization
 - pH
 - Time
 - solids ratios
 - chemical dosages
 - settling characteristics


2ND STAGE OVERVIEW

- Generalized flow sheet




2ND STAGE OPTIMIZATION USING FRESH GIBBSITE

- Effluent sulfate concentration




2ND STAGE RESULTS USING REGENERATED GIBBSITE

- Effluent sulfate concentration-regenerated Gibbsite




2ND STAGE RESULTS

- Effluent aluminum concentration




2ND STAGE RESULTS

- Ettringite crystals in effluent



2ND STAGE RESULTS

- Recovered aluminum sludge sample



TWO-STAGE ADVANCED ETTRINGITE PROCESS - OPEX

- Cost comparison for chemicals and power :
 - With Gibbsite recovery and reuse - \$1.60 - \$1.70 per 1,000 gal
 - Without Gibbsite recovery and reuse - \$8.0 - \$9.0 per 1,000 gal

CONCLUSIONS

- Initial pre-treatment and NF
 - Capable of reducing sulfate to < 150 mg/L
 - More than 98% sulfate rejection was achieved

CONCLUSIONS

- Sulfate desaturation and Ettringite removal is a combination of chemical precipitation and adsorption processes
- Important Process parameters:
 - pH
 - Reaction Time
 - Ca : SO₄ ratio & Al : SO₄ ratio
 - Sludge recirculation with an optimized solids ratio
 - Mass of solids in the recycle line per mass of solids generated by the fresh wastewater

CONCLUSIONS

- 1st stage desaturation process:
 - Sulfate from NF reject can be reduced to < 1500 mg/L in presence of a seed material with proper sludge recirculation ratio.
- 2nd stage process:
 - Seed material need be added only once during the crystallization process
 - More than 95% Gibbsite was recovered and reused in the Ettringite process
 - Using 95% recovered Gibbsite and 5% fresh Gibbsite, sulfate reduced to 100 - 200 mg/L